

JUMO GmbH & Co. KG

Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
E-mail: mail@jumo.net
Internet: www.jumo.net

JUMO Instrument Co. Ltd.

JUMO House
Temple Bank, Riverway
Harlow, Essex CM20 2DY, UK
Phone: +44 1279 635533
Fax: +44 1279 635262
E-mail: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.

8 Technology Boulevard
Canastota, NY 13032, USA
Phone: 315-697-5866
1-800-554-JUMO
Fax: 315-697-5867
E-mail: info.us@jumo.net
Internet: www.jumousa.com



JUMO MIDAS C08

OEM pressure transmitter - basic

Applications

- Compressors
- Machine and system construction
- Industrial pneumatic uses
- Commercial vehicles
- Building services

Brief description

This pressure transmitter is used as a basic product of the MIDAS family in applications requiring reliable implementation of measurement tasks that are stable over a long time with an excellent price-to-performance ratio. Beyond the basic product, the MIDAS family offers a solution for every application.

The innovative and patented sensor design of the internally developed ceramic sensor ensures outstanding long-term stability < 0.2%. Relative pressures from 1.6 bar to 60 bar can be measured in gaseous or liquid measuring materials.

Customer benefits

• Process safety

Special design features give the pressure transmitter extraordinary vibration resistance, facilitating use under high vibration loads such as those common in commercial vehicles. Other features that ensure the highest level of quality include a fully automatic measuring and calibrating system, the diagnostic function of the circuit and a 100% final inspection.

• Economical

The Quickon fast connection system allows for reliable installation with less effort. Contacting by the spring contacts is ensured specifically in case of temperature fluctuations. This electrical connection can be used to shorten assembly times, thereby reducing costs by 60% compared to conventional types of connections.

• Diversity

Universal application ensures a wide selection of measurement ranges, process connections and electrical connections.



Type 401002 with QUICKON



Type 401002 with M12x1 connector

Key features

- Long-term stability < 0.2%
- A new level of quality for the OEM sector
- 60% faster device installation with the Quickon fast-connection system
- Temperature compensation range expanded by 50% to -20 to +100 °C
- Vibration performance 2.5 times better than the industry standard
- Made in Germany

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 E-mail: mail@jumo.net
 Internet: www.jumo.net

JUMO Instrument Co. Ltd.
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex CM20 2DY, UK
 Phone: +44 1279 635533
 Fax: +44 1279 635262
 E-mail: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 8 Technology Boulevard
 Canastota, NY 13032, USA
 Phone: 315-697-5866
 1-800-554-JUMO
 Fax: 315-697-5867
 E-mail: info.us@jumo.net
 Internet: www.jumousa.com



Technical data

General information

Reference conditions	DIN 16086 and DIN EN 60770
Sensor	
Principle of measurement	Thick film on ceramic body (piezoresistive)
Permissible load change	> 10 million, 0 to 100 % measurement range
Location	
Mounting location	Any
Calibration location	Device standing vertically, process connection on bottom

Measuring range

Relative pressure	The measurement ranges start at 0 bar									
Measuring range	1.6	2.5	4	6	10	16	25	40	60	bar
Overload capacity ^a	6	6	12	12	20	50	50	120	120	bar
Bursting pressure	12	12	25	25	38	75	75	200	200	bar
Relative pressure										
Measuring range	-1 to 0.6	-1 to 1.5	-1 to 3	-1 to 5	-1 to 9	-1 to 15	-1 to 24			bar
Overload capacity ^a	6	6	12	12	20	50	50			bar
Bursting pressure	12	12	25	25	38	75	75			bar

^a All pressure transmitters are vacuum-proof

Output

Analog output ^a	
Electrical current	
Output 405	4 to 20 mA, 2 wires
Voltage	
Output 412	DC 0.5 to 4.5 V, 3 wires, ratiometric 10 to 90% of the supply voltage
Output 415	DC 0 to 10 V, 3 wires
Output 418	DC 1 to 5 V, 3 wires
Output 420	DC 1 to 6 V, 3 wires
Step response time	
T ₉₀	≤ 2 ms
Burden	
Electrical current	
4 to 20 mA, 2 wires	$R_L \leq (U_B - 8 \text{ V}) / 0.02 \text{ A } (\Omega)$
Voltage	
DC 0.5 to 4.5 V, 3 wires	$R_L \geq 5 \text{ k}\Omega$
DC 0 to 10 V, 3 wires	$R_L \geq 10 \text{ k}\Omega$
DC 1 to 5 V, 3 wires	$R_L \geq 10 \text{ k}\Omega$
DC 1 to 6 V, 3 wires	$R_L \geq 10 \text{ k}\Omega$

^a Additional outputs are available on request.

Mechanical properties

Process connection	
Material	Stainless steel 304
For plug connection, process connection 383	Nickel-plated brass
Process seal	
Internal material ^a	
Seal 600	EPDM
Seal 601	FPM, standard
Seal 602	CR
Seal 604	FFPM
Seal 609	NBR
External material ^a	
for G1/4, Process connection 521	FPM

JUMO GmbH & Co. KG

Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
E-mail: mail@jumo.net
Internet: www.jumo.net

JUMO Instrument Co. Ltd.

JUMO House
Temple Bank, Riverway
Harlow, Essex CM20 2DY, UK
Phone: +44 1279 635533
Fax: +44 1279 635262
E-mail: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.

8 Technology Boulevard
Canastota, NY 13032, USA
Phone: 315-697-5866
1-800-554-JUMO
Fax: 315-697-5867
E-mail: info.us@jumo.net
Internet: www.jumousa.com



Sensor	
Material	Ceramic Al ₂ O ₃ 96%
Enclosure	
Material	Stainless steel 304
Electrical connection	
Material	
Fixed cable, Electr. connection 11	PBT-GF30, PVC
QUICKON, Electr. connection 23	PBT-GF30
Round plug M12x1, Electr. connection 36	PBT-GF30, stainless steel 303L
Bayonet connector, Electr. connection 53	PBT-GF30
Terminal box, Electr. connection 61	PBT-GF30, PA, silicon
Weight	70 g with process connection 502 (G1/4)

- ^a Other materials are available on request.
Note the resistance of the selected sealing material!

Ambient conditions

Permissible temperatures	
Medium	-20 to +125 °C, on request up to -40 to +135 °C
Environment	-20 to +85 °C, on request up to -40 to +125 °C
Storage	-40 to +125 °C
Permissible relative humidity	
Operation	100% rel. humidity, incl. condensation on the outer sleeve of the instrument
Storage	90% relative humidity, no condensation
Permissible mechanical loading	
Vibration strength ^a	50 g, 10 to 2000 Hz
Shock resistance ^b	50 g for 3 ms 100 g for 2 ms
Electromagnetic compatibility	
Interference emission ^c	Class B
Interference immunity ^d	Industrial requirements
Protection ^e	
Fixed cable, Electr. connection 11	IP67
QUICKON, Electr. connection 23	IP67
Round plug M12x1, Electr. connection 36	IP67
Bayonet connector, Electr. connection 53	IP67, on request IP69
Terminal box, Electr. connection 61	IP65

^a IEC 60068-2-6

^b IEC 60068-2-27

^c EN 61326-2-3

^d EN 61326-2-3

^e EN 60529 (with suitable mating piece when connected)

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 E-mail: mail@jumo.net
 Internet: www.jumo.net

JUMO Instrument Co. Ltd.
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex CM20 2DY, UK
 Phone: +44 1279 635533
 Fax: +44 1279 635262
 E-mail: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 8 Technology Boulevard
 Canastota, NY 13032, USA
 Phone: 315-697-5866
 1-800-554-JUMO
 Fax: 315-697-5867
 E-mail: info.us@jumo.net
 Internet: www.jumousa.com



Accuracy

Relative pressure	
Linearity^a	0.25% of end val.
Accuracy at +20°C ^b at -10 to +85°C ^c at -20 to +100°C ^c	0.35% of end val. 0.5% of end val. 1% of end val.
Long-term stability^d	0.2% of end val. per year

^a Linearity based on limit point setting

^b Includes: linearity, hysteresis, repeatability, deviation from initial and final values of measuring range

^c Includes: linearity, hysteresis, repeatability, deviation from initial and final values of measuring range, thermal effect on initial value of measuring range and span.

^d with reference conditions to EN 61298-1

Auxiliary power

Supply voltage U_B^a 4 to 20 mA, 2 wires, Output 405 DC 0.5 to 4.5 V, 3 wires, Output 412 DC 0 to 10 V, 3 wires, Output 415 DC 1 to 5 V, 3 wires, Output 418 DC 1 to 6 V, 3 wires, Output 420	DC 8 to 30 V, Nominal power supply DC 24 V DC 3 to 5.25 V, Nominal power supply DC 5 V DC 11.5 to 30 V, Nominal power supply DC 24 V DC 8 to 30 V, Nominal power supply DC 24 V DC 8 to 30 V, Nominal power supply DC 24 V
Power consumption 4 to 20 mA, 2 wires, Output 405 DC 0.5 to 4.5 V, 3 wires, Output 412 DC 0 to 10 V, 3 wires, Output 415 DC 1 to 5 V, 3 wires, Output 418 DC 1 to 6 V, 3 wires, Output 420	≤ 25 mA ≤ 2 mA ≤ 3 mA ≤ 3 mA ≤ 3 mA
Reverse polarity protection	YES
Circuit	SELV

^a Residual ripple: Peak voltages must **not** exceed or fall below the values specified for the supply voltage!





JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 E-mail: mail@jumo.net
 Internet: www.jumo.net

JUMO Instrument Co. Ltd.
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex CM20 2DY, UK
 Phone: +44 1279 635533
 Fax: +44 1279 635262
 E-mail: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 8 Technology Boulevard
 Canastota, NY 13032, USA
 Phone: 315-697-5866
 1-800-554-JUMO
 Fax: 315-697-5867
 E-mail: info.us@jumo.net
 Internet: www.jumousa.com



Connection diagram

Connection			Terminal assignment ^a				
							
			11 Fixed cable	23 Quickon	36 Round plug M12x1	53 Bayonet	61 Terminal box
4 to 20 mA, 2 wires, output 405							
Power supply	DC 8 to 30 V	UB/S+ 0 V/S-	White Brown	1 3	1 3	1 2	1 2
DC 0.5 to 4.5 V, ratiometric, output 412							
Power supply	DC 3 to 5.25 V	UB 0 V/S- S+	White Brown Yellow	1 2 3	1 2 3	1 2 3	1 2 3
DC 0 to 10 V DC, 3 wires, output 415							
Power supply	DC 11.5 to 30 V	UB 0 V/S- S+	White Brown Yellow	1 2 3	1 2 3	1 2 3	1 2 3
DC 1 to 5 V DC, 3 wires, output 418 DC 1 to 6 V DC, 3 wires, output 420							
Power supply	DC 8 to 30 V	UB 0 V/S- S+	White Brown Yellow	1 2 3	1 2 3	1 2 3	1 2 3

^a Illustration: Connection on pressure transmitter

Color assignment: Round plug M 12		1 bn Brown	4 bk Black	The color assignment applies only to A-coded standard cables!
		2 wh White	5 gy Gray	
		3 bu Blue		

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 E-mail: mail@jumo.net
 Internet: www.jumo.net

JUMO Instrument Co. Ltd.
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex CM20 2DY, UK
 Phone: +44 1279 635533
 Fax: +44 1279 635262
 E-mail: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 8 Technology Boulevard
 Canastota, NY 13032, USA
 Phone: 315-697-5866
 1-800-554-JUMO
 Fax: 315-697-5867
 E-mail: info.us@jumo.net
 Internet: www.jumousa.com



Dimensions

Electrical connection

11 Fixed cable	23 Quickon	36 Round plug M12x1	53 Bayonet connector	61 Terminal box

Process connection

383 Plug-in screw connection Ø6 mm	502 G1/4	504 G1/2	511 1/4 - 18 NPT

A = Plug-in screw connection for DN6 hose (external diameter 6 mm)

521 G1/4	547 Rp 1/8	562 7/16 UNF	

B = Profile seal G1/4

JUMO GmbH & Co. KG

Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
E-mail: mail@jumo.net
Internet: www.jumo.net

JUMO Instrument Co. Ltd.

JUMO House
Temple Bank, Riverway
Harlow, Essex CM20 2DY, UK
Phone: +44 1279 635533
Fax: +44 1279 635262
E-mail: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.

8 Technology Boulevard
Canastota, NY 13032, USA
Phone: 315-697-5866
1-800-554-JUMO
Fax: 315-697-5867
E-mail: info.us@jumo.net
Internet: www.jumousa.com



Order details

401002	(1) Basic type
	JUMO MIDAS C08
	OEM pressure transmitter - Basic
	(2) Basic type extension
000	None
999	Special design
	(3) Relative pressure measurement range
	Overpressure
455	0 to 1.6 bar
456	0 to 2.5 bar
457	0 to 4 bar
458	0 to 6 bar
459	0 to 10 bar
460	0 to 16 bar
461	0 to 25 bar
462	0 to 40 bar
463	0 to 60 bar
	Negative overpressure
479	-1 to +0.6 bar
480	-1 to +1.5 bar
481	-1 to +3 bar
482	-1 to +5 bar
483	-1 to +9 bar
484	-1 to +15 bar
485	-1 to +24 bar
999	Special measurement range
	(4) Output
405	4 to 20 mA, 2 wires
412	DC 0.5 to 4.5 V, 3 wires, ratiometric
415	DC 0 to 10 V, 3 wires
418	DC 1 to 5 V, 3 wires
420	DC 1 to 6 V, 3 wires
	(5) Process connection
383	Plug-in screw connection ø6 mm
502	G 1/4 DIN EN 837
504	G 1/2 DIN EN 837
511	1/4-18 NPT DIN EN 837
521	G 1/4 DIN 3852 T11
547	Rp 1/8
562	7/16 UNF
	(6) Process connection material
20	Stainless steel
	(7) Seal material
600	EPDM
601	FPM ^a
602	CR
604	FFPM
609	NBR
999	Special material

^a Standard

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 E-mail: mail@jumo.net
 Internet: www.jumo.net

JUMO Instrument Co. Ltd.
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex CM20 2DY, UK
 Phone: +44 1279 635533
 Fax: +44 1279 635262
 E-mail: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 8 Technology Boulevard
 Canastota, NY 13032, USA
 Phone: 315-697-5866
 1-800-554-JUMO
 Fax: 315-697-5867
 E-mail: info.us@jumo.net
 Internet: www.jumousa.com



(8) Electrical connection

- 11 Fixed cable, 2 m^a
- 23 Quickon
- 36 Round plug M12x1
- 53 Bayonet connector DIN 72585-A1-3.1-Sn/K1
- 61 Terminal box DIN EN 175301-803, Form A, ex DIN 43650

(9) Extra codes

- 000 None
- 591 Throttle in pressure channel
- 624 Free of oil and grease
- 630 Enlarged pressure channel ø8 mm^b

^a Other lengths on request

^b Only for process connection 511, 521 and material of FPM seal

	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(9)									
Order code		/		-		-		-		/		,	...						
Sample order	401002	/	000	-	460	-	412	-	504	-	20	-	600	-	36	/	591	,	624

Stock instruments

Delivery in 3 working days after receipt of order

Type	Version	Part No.
401002/000-456-405-502-20-601-23/000	0 to 2.5 bar, 4 to 20 mA, G 1/4, FPM, Quickon	00542718
401002/000-458-405-502-20-601-23/000	0 to 6 bar, 4 to 20 mA, G 1/4, FPM, Quickon	00542740
401002/000-459-405-502-20-601-23/000	0 to 10 bar, 4 to 20 mA, G 1/4, FPM, Quickon	00542743
401002/000-460-405-502-20-601-23/000	0 to 16 bar, 4 to 20 mA, G 1/4, FPM, Quickon	00542746
401002/000-461-405-502-20-601-23/000	0 to 25 bar, 4 to 20 mA, G 1/4, FPM, Quickon	00542748
401002/000-456-405-502-20-601-61/000	0 to 2.5 bar, 4 to 20 mA, G 1/4, FPM, terminal box	00546113
401002/000-457-405-502-20-601-61/000	0 to 4 bar, 4 to 20 mA, G 1/4, FPM, terminal box	00546119
401002/000-458-405-502-20-601-61/000	0 to 6 bar, 4 to 20 mA, G 1/4, FPM, terminal box	00546120
401002/000-459-405-502-20-601-61/000	0 to 10 bar, 4 to 20 mA, G 1/4, FPM, terminal box	00546121
401002/000-460-405-502-20-601-61/000	0 to 16 bar, 4 to 20 mA, G 1/4, FPM, terminal box	00546122
401002/000-461-405-502-20-601-61/000	0 to 25 bar, 4 to 20 mA, G 1/4, FPM, terminal box	00546123
401002/000-462-405-502-20-601-61/000	0 to 40 bar, 4 to 20 mA, G 1/4, FPM, terminal box	00546124
401002/000-481-405-502-20-601-61/000	-1 to +3 bar, 4 to 20 mA, G 1/4, FPM, terminal box	00546125

Accessories

Designation	Part No.
4-pin cable connector, straight M12x1 with 2-m PVC cable	00404585
4-pin cable connector, angled M12x1 with 2-m PVC cable	00409334