

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14,
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 E-mail: mail@jumo.net
 Internet: www.jumo.net


JUMO Instrument Co. Ltd.
 JUMO House
 Temple Bank, Riverway
 Harlow - Essex CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 63 52 62
 E-mail: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 8 Technology Boulevard
 Canastota, NY 13032, USA
 Phone: 315-697-JUMO
 1-800-554-JUMO
 Fax: 315-697-5867
 E-mail: info@jumo.us
 Internet: www.jumo.us



Pressure separator with male thread ISO 228/1 or ANSI B 1.201 Type 409782


Diaphragm pressure separator ISO 228/1



Technical data

Process connection thread G	Nominal pressure bar	Recommended min. pressure range bar	Temperature coefficient mbar/10°C	Weight (without meas. device) kg	Dimensions [mm]					
					a/f	d _M	d ₁	d	d ₂	k
1" pipe B	PN600	above 10	+20	0.40	41	28	29	39	a/f 41	21
1½" pipe B		above 0.4	+12	1.08		38	44	55	58	30
2" pipe B		above 0.1	+3	1.95	65	46	56	68	78	

Diaphragm pressure separator ANSI B 1.201



Technical data

Process connection	Nominal pressure bar	Recommended min. pressure range bar	Temperature coefficient mbar/10°C	Weight (without meas. device) kg	Dimensions [mm]			
					a/f	d _M	d ₂	k
1" NPT	PN600	above 10	+20	0.55	41	24	(a/f 41)	28
1½" NPT		above 0.4	+12	1.00	46	32	52	30
2" NPT		above 0.1	+6	1.92	65	38	78	

JUMO GmbH & Co. KG

Delivery address: Mackenrodtstraße 14,
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
E-mail: mail@jumo.net
Internet: www.jumo.net

JUMO Instrument Co. Ltd.

JUMO House
Temple Bank, Riverway
Harlow - Essex CM20 2DY, UK
Phone: +44 1279 63 55 33
Fax: +44 1279 63 52 62
E-mail: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.

8 Technology Boulevard
Canastota, NY 13032, USA
Phone: 315-697-JUMO
1-800-554-JUMO
Fax: 315-697-5867
E-mail: info@jumo.us
Internet: www.jumo.us

**Order details**

(1) Basic type	
409782	pressure separator with male thread ISO 228/1 or ANSI B 1.201
(2) Basic type extension	
00	none
(3) Process connection	
572	1" pipe B (ISO 228/1)
570	1½" pipe B (ISO 228/1)
569	2" pipe B (ISO 228/1)
514	1" NPT (ANSI B1.201)
515	1½" NPT (ANSI B1.201)
516	2" NPT (ANSI B1.201)
(4) Nominal pressure in bar	
600	PN600
(5) Material	
20	st. steel
99	special material ¹
(6) Filling liquid	
1	silicone oil
2	halogenized oil
3	vegetable oil
(7) Capillary	
0000	no capillary
0001	with cooling device
1000	1.0 m capillary
1500	1.5 m capillary
2000	2.0 m capillary
3000	3.0 m capillary
5000	5.0 m capillary

	(1)	(2)	(3)	(4)	(5)	(6)	(7)
Order code		/	-	-	-	-	-
Order example	409782	/ 00	- 572	- 600	- 20	- 3	- 1500

¹ please specify in plain text when ordering